SAMSUNG TOUCH SERIES

DEPLOY INTERACTIVE DISPLAYS WITH THREE SIMPLE STEPS

CHOOSE A PANEL AND A TOUCH OPTION

Samsung provides maximum flexibility b enabling interactive

ent	Super-slim MEC Series (32", 40", 46", 55", 75" inches) with high-brightness screens						
	ME32C	ME40C	ME46C	ME55C			
	32"	40"	46"	55"			
	60Hz e-LED BLU	60Hz e-LED BLU	60Hz e-LED BLU	120Hz e-LED BLU			
		-					
)	450 nits	450 nits	450 nits	450 nits			

5000:1

5000:1

53.9" x 33.4" x 7.8"

59 lbs.

73.9 lbs.

36.2 lbs.

48.5 lbs.

5000:1

40.2" x 24.3" x 5.1"

23.4 lbs.

27.8 lbs.

5000:1

28.9" x 17.1" x 1.2"

32.8" x 20.4" x 4.7

14.8 lbs.

18.3 lbs.

Affordable ED Series (65", 75" inches) with edge-lit LED								
ED65C	ED75C							
65"	75"							
120Hz LED BLU	240Hz LED BLU							
320 nits	320 nits							
4000:1	4000:1							
Analog D-SUB	Analog D-SUB							
HDMI1	HDMI1							
	1							
N/A	N/A							
57.8" x 33.4" x 2.6"	65.9" x 37.8" x 2.5"							
63" x 38.6" x 8.5"	72.9" x 43.3" x 19.2"							

63.4 lbs.

107.4 lbs.



Touch interactivity is enabled by attaching a compatible Touch Overlay module (sold separately). The module is made with scratch-resistant glass and specially coated so that writing feels just like it does on conventional whiteboards. The Touch Overlays also have an anti-glare film for optimal viewing - even in bright light.

36.3" x 21.2" x 1.2" 41.6" x 24.2" x 1.2" 49.1" x 28.4" x 1.2" 46" x 28.4" x 5.5"

28.9 lbs.

36.8 lbs.

Touch Overlay Model		CY-TM32LCA	CY-TM40LCA	CY-TM46LCA	CY-TM55LCC	CY-TE65	CY-TE75		
Compatible Panel			ME32C	(ME40C)	ME46C	(ME55C)	MD65C, ED65C	ED75C	
		32"	40"	46"	55"	65"	75"		
Mechanical Spec	Dimension	Set	29.6" x 17.6" x 1.3"	37" x 21.7" x 1.3"	42.4" x 27.7" x 1.3"	49.9" x 29" x 1.3"	59.8" x 35.2" x 1.8"	68.4" x 40" x 1.8"	
		Package	33.1" x 21" x 4"	40.5" x 25.2" x 4"	28.9" x 46.7" x 4"	54.2" x 33.2" x 4"	65.1" x 29.8" x 10.4"	74.4" x 44.7" x 10.4	
	Weight	Set	9.3 lbs.	12.8 lbs.	16.1 lbs.	20.9 lbs.	48.9 lbs.	58.6 lbs.	
		Package	11.9 lbs.	15.7 lbs.	20.3 lbs.	26.9 lbs.	64.8 lbs.	80.5 lbs.	
	Glass Thickness (mm)		2.8	2.8	2.8	2.8	3.2	3.2	
	Glass Film		AG (Front), PET (Rear)						
	Glass Reflection Rate		≤10%	≤10%	≤10%	≤10%	≤10%	≤10%	
	Glass Haze		≤15%	≤15%	≤15%	≤15%	≤15%	≤15%	
	Frame Material		Aluminum Extrusion						
	Bezel Width (mm)		26.5	23.6	26.5	26.5	42.7	42.7	
Touch	Touch Technology		IR	IR	IR	IR	IR	IR	
	Response Time		11ms	11ms	14ms	11ms	11ms	11ms	
	Number of Simultaneous Touch		10 Point	10 Point	10 Point	6 Point	6 Point	6 Point	
	Operating System		Windows XP Pro SP3, Windows 7 32/64, Windows 8 32/64, Linux Ubuntu 10.10/11.04, IOS 10.8 or higher						
Accessory	Included	Software	Magic/WB Basic (e-Board S/W)	MagicIWB Basic (e-Board S/W)	MagicIWB Basic (e-Board S/W)	MagicIWB Basic (e-Board S/W)	MagicIWB Basic (e-Board S/W)	MagicIWB Basic (e-Board S/W)	
		Hardware	N/A	N/A	N/A	N/A	Pen Tray (Including USB Hub with 1 Up, 2 Down), Pen	Pen Tray (Including USB Hub with 1 Up, 2 Down), Pen	

The 65" and 75" Touch Overlay modules include a pen tray attachment and a stylus pen. The pen tray has two integrated USB slots on the side for connecting USB flash drives for easy file uploads. The stylus pen can be used for fine detail drawing and writing.

