




47"|55" Sunshine Outdoor LCD TV


Our Sunshine outdoor LCD TV series is the perfect all-season solution for any outdoor event. With no maintenance and the highest operating ratings in its class, this is truly the total package solution for your outdoor entertainment needs

Dimensions

All dimensions = inch (mm)


47" EPONT VIEW 55"





50.39° FRONT VIEW





TV Controller Features

ANALOG TV DIGITAL TV

PICTURE MODE

MTS

PICTURE ADJUSTMENT

COLOR TEMPERATURE

SCREEN ADJUSTMENT

CLOCK, SLEEP TIMER

NOISE REDUCTION

ELECTRONIC PROGRAM GUIDE

Additional Features

Integrated thermal management allowing operating temps of -24 to 124 dearees F

Dependable materials and construction protect against weather, discoloration and impact

Waterproof external speakers

Anti-Reflective, Impactresistant glass

Specifications

ATSC, MPEG4, QAM256, H.264

Brightness/Contrast/Saturatio/ Tint/ Sharpness/Noise reduction

Standard, Dynamic, Personal, Soft

Cool, Normal, Warm

Normal/Wide/Zoom

Yes

Vos

Yes

Yes

LCD DIsplay

SCREEN SIZE	47" diagonal 55" diagonal
ASPECT RATIO	16:9
RESOLUTION	1920 X 1080
BRIGHTNESS	700cd/m²
CONTRAST RATIO	1000:1
VIEWING ANGLE	178° Vertical/Horizontal
RESPONSE TIME	9 ms (Gray to Gray)
REFRESH RATE	120 hz

Environmental

Livioninental		
OPERATING TEMPERATURE	-24°F to 124°F	
STORAGE TEMPERATURE	-40°F to 140°F	
RATINGS	IP65 AND NEMA 4X	
SAFETY/EMC	FCC Class B	

STORAGE TEMPERATURE	-40°F to 140°F	
RATINGS	IP65 AND NEMA 4X	
SAFETY/EMC	FCC Class B	
Mechanical		

SIZE (W x H x D)	43.58" x 25.67" x 5.52" (1107 x 652 x 140mm)	50.39" X 29.56" X 5.85" (1280 X 751 X 149mm)	
COLOR	Black		

GLASS	Anti-reflective, UV Protection, Safety
VESA® PATTERN	600 x 400mm
NET WEIGHT	85lb (39kg) 119lb (54kg)

Input/Output Connections

TV INPUT	Coax, 75 ohm (x1)
VGA INPUT	15 pin D-SUB (x1)
HDMI INPUT	HDMI (x3), 480i, 480p, 720p, 1080i, 1080p
S-VIDEO INPUT	Mini DIN (x1)
CVBS INPUT	RCA (x1)
YPBPR INPUT	RCA (x1), 480i, 480p, 720p, 1080i, 1080p
STEREO AUDIO INPUT	3.5 mm (x1)
STEREO AUDIO INPUT	RCA (x1)
AUDIO OUTPUT	3.5 mm (x1)
SPEAKERS	Included, 10W x 2 at 8Ω
USB	Yes
RS232	DB-9 (Male)

Power

AC INPUT	90 VAC to 240 VAC, 47 to 63 HZ
POWER CONSUMPTION	47" Display – 126W (Nominal)
	55" Display – 140W (Nominal)